

IDF510 imagePROGRAF[®]



TECHNICAL DOCUMENTS LARGE-FORMAT PRINTING





iPF510 SPECIFICATIONS



Print-Head PF-03 Technology FINE (Full-Photolithography Ink-Jet Nozzle Engineering) Print Resolution (Max.) 2400 x 1200 dpi Line Accuracy* ±0.1% or Less Minimum Line Weight** 0.02mm Number of Nozzles Matte Black: 5,120 Nozzles Other Colors: 2,560 Nozzles per Color **Droplet Size** 4 Picoliter Nozzle Pitch (Head Resolution) 1200 dpi x Two Rows **Print-Head Swath** 1.07 inch Ink Type Dye Cyan (C), Magenta (M), Yellow (Y), Black (BK) Pigment Matte Black (MBK) – Two Channels Ink Tank PEI-102 Ink Tank Capacity*** 130ml per Tank Number of Colors 5 Ink Sunnly Method Tubing System **Nozzle Recovery System** Non-firing Nozzle Detection and Compensation **Printer Controller** L-COA Controller **Printer Memory** 192MB Media Feed Top-Loading Manual Feed, Front-Loading Manual Feed, Cassette, Optional Top-Loading Roll Feed Media Width Roll Feed.* Manual Feed 8" – 17" (203mm – 432mm) Cassette 8" – 17" (203mm – 432mm) **Printable Margins** Roll Feed* All Sides: 0.12" (3mm) or 0" for Borderless Cassette All Sides: 0.12" (3mm) Manual Feed Left, Right, Trailing: 0.12" (3mm), Leading: 0.90" (23mm) or 0.12" (3mm) **Minimum Printable Media Length** Roll Feed* 8.0" (203mm) Cassette 10.0" (254mm) Top-Loading Manual Feed 10.98" (279mm) Front-Loading Manual Feed 20.5" (520mm)

Roll Feed* 59' (18m) Cassette 23.38" (594mm) Manual Feed Top: 24" (609mm) 63" when roll feed unit is attached Front: 36" (914mm) Cassette Capacity (Plain Paper) Casselle Capacity (rrain raper) 250 Sheets (Letter-Sized), 100 Sheets (up to 13" × 19" Sized), 50 Sheets (up to 17" x 22" Sized) Borderless Printing Widths (Roll Media Only)[◆] 10", 13", 14", 16", 17", B4 (10.12"/257mm), A2 (16.54"/420mm) **Media Cutter** Durable Rotary Blade Media Thickness Cassette 0.08 – 0.3mm (3.2 – 11.8mil) Top-Loading Manual Feed 0.07 – 0.8mm (3.2 – 31.4mil) Front-Loading Manual Feed 0.5 – 1.5mm (19.6 – 59.0mil) Roll Feed[◆] 0.07 - 0.8mm (2.8 - 31.4mil) Media Core Sizes: 2" or 3" Core (2/3" Core Adapter Included) Maximum Roll Outer Diameter: 5.9" (150mm) Software **Printing Software** imagePROGRAF Printer Driver for Windows/Mac, HDI Driver^{††}, Printer Driver Extra Kit for Windows/ Mac (Free Layout, Color imageRUNNER[®] Enlargement Copy, Advanced Preview), Print Plug-in for Microsoft Word/Excel/PowerPoint for Windows, Digital Photo Front-Access for Windows, PosterArtist Lite for Windows Utilities Media Configuration Tool, GARO Device Setup Utility **Device Status** GARO Status Monitor, Remote UI Printer Language GARO, HP-GL/2, HP RTL **Operating Systems** Windows[®] 2000/XP/ Server 2003/Windows Vista[®] Macintosh[®] OS 9/10 (PowerPC or Intel) Interface Standard (Built-in) USB 2.0 Hi-Speed, 10/100Base-T/TX Optional IEEE1394 (FireWire) Acoustic Noise Operation 52dB (A) or Less Standby 35dB (A) or Less **Acoustic Power** 6.6 Bels Power Supply AC 100–120V (50-60Hz) Power Consumption Maximum 100W or Less Standby 6W or Less

Maximum Print Length¹

 for AutoCAD or AutoCAD LT 2000/2000/2002/ 2003/2004/2005/2003 Server and for Macintosh, Auto Layout, and imageRUNNER Linking Function
For imagePROGRAF Printer Driver. For printing from PostScript applications such as Adobe[®] Illustrator[®] or QuarkXPress[™], please use a PostScript[®] compatible RIP package. For a list of Canon recommended RIP packages, please consult with Canon Alliance and Industry Market program list of RIP vendors.
Catton imageANYWARE

Certifications

Temperature

Weight

Options

Operational Environment

59 – 86 F° (15 – 30 C°)

Relative Humidity 10 – 80% (No Condensation)

Printer Dimensions (H x W x D)

Approx. 86 lb. (39kg)

UL®, FCC Class B, ENERGY STAR®

IEEE1394 Expansion Board (EB-05)

Auto Roll Feed Unit (RU-02)

Cabinet Stand (CB17-01) Roll Holder Set (RH2-11)

Desktop Basket (BU-02)

Maintenance Cartridge (MC-05)

Printer Stand (ST-11)

Ink Tanks (PFI-102)

Registration Card

drawing only.

specified here.

User Replaceable Items Print-Head (PF-03)

What's In The Box

12.5" x 32.2" x 28.9" (317mm x 819mm x 733mm)

Printer, User Software CD (Printer Driver, HDI Driver, Utilities), Application CDs (PosterArtist Lite,

2), 6 Starter Ink Tanks (MBK x2, Cvan, Magenta, Yellow, Black), 2° Core Media Spool, Print Head, Maintenance Cartridge, Built-in Ethernet/USB 2.0 Interface, Quick Setup Guide (Poster), Printer

environmental conditions. Applies to media for line

The starter ink tanks initially packaged with the printer

† The maximum printable length varies depending on the

application, OS, and RIP used. The maximum printable

are not the same capacity as the replacement ink tanks

Reference Guide (Booklet), Power Cord,

* After user adjustment and under the same

Theoretical value based on data resolution

Requires optional roll feed unit

length from Printer Driver is 50 feet.

1-800-OK-CANON www.usa.canon.com

Canon U.S.A., Inc. One Canon Plaza Lake Success, NY 11042

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, IMAGEPROGRAF, IMAGERUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All referenced product names and other marks are trademarks of their respective owners. Some items may not be available at this time; please check for availability. Specifications and availability subject to change without notice. ©2010 Canon U.S.A., Inc. All rights reserved.



(7W or less when EB-05 is installed)

(Executive Order Compliant)

Power Off 1W or Less







